



# EloPOS Z10 with Intel®

All-in-One POS System



**Compact Form Factor**

**Powerful Intel  
Processing**



**Enterprise-Grade  
Support**

## Product Overview

Built on Elo's unified architecture, the EloPOS Z10 delivers a powerful, minimalistic design to help optimize checkout in compact spaces without losing inches on your point-of-sale terminal. Complete with a 15.6-inch Full HD interactive display, I/O hub, contained cable routing, your choice of Windows 10, ChromeOS Flex or Linux (SuSE, Ubuntu and Red Hat) and an optional interactive customer-facing display, the EloPOS Z10 delivers one of the slimmest POS systems to the market. Start changing the way customers and employees interact by deploying a new generation of interactive point-of-sale technologies.

**Compatible with I-Series Slate 15.6"  
Full HD AiO touchscreen computer**

**Add Elo's 0702L Touchscreen Monitor to  
the back of the stand to create a point of  
interaction for customers**

**Available with Windows 10, ChromeOS  
Flex and Linux operating systems**

## EloPOS Z10 with Intel

Specifications	
Bezel Color	Grey
Diagonal Size	15.6" (396.24mm)
Active Display Area	13.55" x 7.62" / 344 mm x 194 mm
Resolution	1920 x 1080 @ 60Hz
Touch Technology	TouchPro® PCAP (Projected Capacitive) - up to 10 touches
Aspect Ratio	16:9
Number of Colors	16.2M
Brightness	LCD Panel: 300 nits; PCAP: 255 nits
Response Time	25 ms
Viewing Angle	Horizontal: ±85° or 170° total / Vertical: ±85° or 170° total
Contrast Ratio	1000:1
Processor	Intel® Pentium® Processor J6426
Video	Intel UHD Graphics
BIOS	AMI
Memory	4GB
Storage	Standard: 64GB; Value: 32GB
Wireless LAN	802.11 a/b/g/n/ac/ax 2.4GHz and 5GHz and 6GHz
Bluetooth	Bluetooth 5.2
Antenna	2T2R design
Webcam	8MP, Max Resolution: 1920x1080 30fps, with Auto Focus
MIC	Digital Microphone
TPM	TPM2.0
Speakers	Two 2W internal speakers
I/O Ports	Display Head Interface: USB-C Connector, Supports USB 2.0/3.0, DP output, (Requires 20V/40W USB-C Power Delivery 2.0 if not using I/O Hub for power) I/O Hub: DC Input, 4 x USB-A 3.0, RJ45 Ethernet LAN (Gigabit) (w/o Wake on Lan at S5 support)
Operating System	No Operating System Microsoft Windows 10 IoT Enterprise LTSC 64-bit
Languages	Windows 10 - 36 Language groups
Control Buttons	Power Button
Power	External 19VDC universal-type power supply brick AC input voltage: 100-240 VAC Input frequency: 50-60 Hz Maximum output power: 65W
Power Consumption	30W
Real-Time Clock	Replaceable CR2450 lithium metal battery
Dimensions (W x H x D)	14.3" x 9.9" x 5.5" / 362.8 mm x 252.7 mm x 139.7 mm
Shipping Dimensions	I-Series 3 Slate with Intel: 18.11" x 12.64" x 7" / 460 mm x 321 mm x 178 mm Z10 POS Stand: 10.1" x 8.8" x 8.7" / 256 mm x 223 mm x 220 mm
Weight	I-Series 3 Slate with Intel: 3.53 lbs / 1.6 kg Z10 POS Stand: 2.52 lbs / 1.14 kg EloPOS Z10 with Intel: 6.05 lbs / 2.74 kg
Shipping Weight	I-Series 3 Slate with Intel: 8.81 lbs / 4 kg Z10 POS Stand: 4.63 lbs / 2.1 kg
Temperature	Operating: 0°C to 35°C / 32°F to 95°F; Storage: -20°C to 60°C / -4°F to 140°F
Humidity	Operating: 10% to 90%; Storage: 0% to 95% (38.7° max wet bulb temperature)
Mounting Options	VESA 75mm
MTBF	50,000 hours demonstrated
Energy Star Certified	ES 8.0
Warranty	I-Series 3 Slate with Intel: 3 years Z10 POS Stand: 2 years
Extended Warranty	I-Series 3 Slate with Intel: 4 YR warranty - Elo P/N: E819598, 5 YR warranty - Elo P/N: E819795 3 YR warranty + AUR - Elo P/N: E820186, 4 YR warranty + AUR - Elo P/N: E820388, 5 YR warranty + AUR - Elo P/N: E820582 Z10 POS Stand: 3 YR warranty - Elo P/N: E375367, 4 YR warranty - Elo P/N: E375573, 5 YR warranty - Elo P/N: E375771 2 YR warranty + AUR - Elo P/N: E375970, 3 YR warranty + AUR - Elo P/N: E376169, 4 YR warranty + AUR - Elo P/N: E376362, 5 YR warranty + AUR - Elo P/N: E376547
Regulatory Approvals	UL/cUL, FCC, CE, CB, NOM, RCM, VCCI, Argentina S-Mark, CCC, SRRC, ANATEL, UKCA
What's in the Box	I-Series 3 Slate with Intel: I Series Slate, IO Hub, NA Power Cord, EU Power Cord, 65W Power Brick, QIG Z10 POS Stand: Z10 POS Stand, 2x M4 x5 screws for attaching the head to the stand, 4x M4 x 18 screws for attaching the CFD, 4x M4 x 10 screws for attaching the plate adapter to head, 1x Hex 4X108 allen wrench for adjusting hinge torque, 1x Back Cover for CFD, 1x Plate Adapter for I-Series 4/5 and I-Series 4 Slate, QIG

## Ordering Information

Family	Part Number	Size	OS	Processor
I-Series 3 Slate with Intel	E983676	15.6-inch	No OS	Intel Elkhart Lake J6426
I-Series 3 Slate with Intel	E983895	15.6-inch	Windows 10	Intel Elkhart Lake J6426
Z10 POS Stand	E767159	N/A	N/A	N/A

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

### Americas

Tel +1 408 597 8000  
elosales.na@elotouch.com

### Europe (EMEA)

Tel +32 16 930 136  
EMEA.Sales@elotouch.com

### Asia Pacific

Tel +86 (21) 3329 1385  
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2024 Elo Touch Solutions, Inc. All rights reserved. 24011AES00184

