

PRINTER

# 

# The Compact and Secure Solution for Issuing Financial Cards in Your Branches

The **Issengo** system combines advanced features, compacity, ease of use and seamless integration in branches. Issengo issues flat debit and credit cards on demand, and complies with international banking associations security guidelines.



#### **Maximum Security**

- Issengo's electromechanical locking system prevents access to the blank and rejected cards, ribbon, and internal parts of the machine. It can be configured for dual access control for increased security.
- The patented Kineclipse® innovation masks any residual sensitive data left on the printing ribbon.



#### **Optimized Footprint**

- The Issengo system is compact and can fit easily into any workspace in your branch.
- The system can be controlled by a completely dematerialized interface, thus not requiring the deployment of a dedicated computer nearby.




#### **Increased Flexibility**

- Issengo can automatically customize a card design in batches or exceptional designs through manual card insertion.
- The Evolis Mosaic SDK is designed to facilitate software integration and allow secure communication with existing information systems.



100-card feeder and slot for single manual card insertion



**ISSENGO** 

- S136 1528 9536 1523 MICKAEL JORN HAN 09/12/18 Without Kineclipse® With Kineclipse®
  - Kineclipse<sup>®</sup> process for masking the residual characters left on the printing ribbon

Electromechanical locking system



8423 9417 6710 0952

ULD FROM 12/22 ULD THRU 01/26

# Main Features

#### Full technical specifications on www.evolis.com

#### **O**General Features

- Direct-to-card dye-sublimation/ Resin thermal transfer
- Edge-to-edge, single or dual-sided printing
- Standard 300 x 300 dpi resolution
- Embedded PC card

#### Printing Performances

- Dual-side:
- Monochrome (KO/KO): 24 s per card
- Color (YMCKO-K): 32 s per card

#### ◎ Interfaces

- Ethernet TCP-IP 10BaseT, 100BaseT (Traffic Led)
- $\cdot\,$  USB A port inside the system

#### Card Management & Specifications

- Feeder capacity: 100 cards (0.76 mm - 30 mil)
- Slot for manual insertion of exceptional designs
- Output hopper capacity: 50 cards (0.76 mm - 30 mil)
- Internal reject tray capacity: 10 cards (0.76 mm - 30 mil)
- Card thickness:
  Feeder : 0.50 1.25 mm (20 - 50 mil), gauge adjustment
- Manual insertion slot: 0.50 - 0.76 mm (20 - 30 mil)
- Card types: PVC cards, composite PVC cards
- Card format: ISO CR80 ISO 7810
   (53.98 mm x 85.60 mm)

#### Additional Encoding Modules

- Available modules:
- Magnetic stripe encoder ISO 7811 HiCo/LoCo, JIS2
- Smart contact station ISO 7816-2
- Contact smart card encoder PC/ SC, EMV 2000-1
- Contactless smart card encoder -ISO 14443A, B, ISO15693, MIFARE, DESFire, HID iCLASS
- Other specific encoders upon request
- Options can be combined
- Factory-installed or installed on site

# O Safety

- Electromechanical locking system with optional dual access control
- Kineclipse<sup>®</sup> process for masking the residual data left on the printing ribbon
- Data encryption (SSL/TLS), supports 3DES and AES-256
- Support for Kensington<sup>®</sup> security lock

# 🔘 Display

• Color touch screen display (2.4")

# © Software

• Evolis Mosaic SDK for remote supervision of the printer, easy integration and secure communication

### © Evolis High Trust<sup>®</sup> Ribbons

To maximize the quality and durability of printed cards, the lifespan of the print head and the overall printer reliability, use Evolis High Trust® ribbons.

- Automatic identification and setting
- Delivered in a drop-in cassette for easy handling
- Ribbon saver for monochrome printing

List of ribbons available on www.evolis.com

#### Eco-Friendly Design, Certifications & Statement of Compliance

- Standby mode & reduced energy consumption
- · CE, FCC, ICES, EAC
- RoHS

#### O Size & Weight

- Size (H x W x D):
- 247 x 211 x 392 mm (9.72" x 8.31" x 15.43")
- Weight: 6.3 kg (13.23 lbs)

# O Warranty

- 2-year warranty (printer and print head)<sup>2</sup>
- Warranty extension available as an option



#### A GLOBAL PROVIDER OF IDENTIFICATION SOLUTIONS

- Worldwide leader in card personalization systems for decentralized issuance
- International expertise and local support through a network of 400 distributors in 140 countries
- A unique ability to meet specific customer specifications with a Project department dedicated to design and construction of tailor-made solutions
- © Evolis is ISO 9001 certified, which reflects our comprehensive approach, both in terms of quality and continuous improvement

# www.evolis.com

HQ / EUROPE - MIDDLE-EAST - AFRICA Evolis - 14 avenue de la Fontaine - ZI Angers-Beaucouzé 49070 - Beaucouzé - FRANCE T +33 (0) 241 367 606 - F +33 (0) 241 367 612 - info@evolis.com

USA - CANADA Evolis Inc. - Providence - RI - USA - evolisinc@evolis.com

LATIN AMERICA Evolis Inc. - Fort Lauderdale - FL - USA - evolisinc@evolis.com

ASIA - PACIFIC Evolis Asia Pte Ltd - Singapore - evolisasia@evolis.com

CHINA Evolis China - Shanghai - evolischina@evolis.com

INDIA Evolis India - Mumbai - evolisindia@evolis.com