

RT420B LABEL PRINTER

Xprinter 4"/100mm Direct Thermal label/barcode - easy to use & reliable

- Auto calibrates to label size with high quality auto double sensor Japanese print head
- Long life, great reliability. Estimated 300,000 x 100mm label print head life
- Adjustable width 25-108mm, rolls or folded
- Shelf, price, product, shipping, stock and barcode labels. It does them all
- Standard Seagull printer drivers, Multiple interfaces, USB, Serial, LAN.
- Works with all major shipping labels, Fedex, DPD, UPS etc



RT420B Label Printer Data

Print details		Power supply	
Print Method	Direct Thermal, front exit	Type - external	Inline switch mode
Print speed	152mm/sec	Output cable	1.5M DC lead Kikon male
Resolution (Dots/inch)	203 DPI	Power input	100-240v/50-60 Hz
Paper/label specification		Power rating	24 volts 2.5 Amps
Max Width (nominal)	4.25"/108mm max	Input cable	1.8M IEC lead UK 3 pin
Media core size	25.4-76.2mm	Processor, memory, fonts	
Label thickness	0.06-0.25mm	CPU	32 Bit RISC
Label length	10mm-1778mm	Memory	8MB Flash/8B SDRAM
Paper roll width	20mm-115mm	Internal fonts	8 bmp AN+ Windows
Label Media type	Continuous, gap, black mark, rolls, fan-fold and punched hole	1D and 2D barcodes	All common 1D and 2D barcodes and QR codes
Label roll capacity	127mm	Emulation	
Interface connections		Emulation modes	TSPL, EPL, ZPL, DPL2
Ethernet standard	RJ45 socket	Dimensions & Weights	
USB standard	Type B, cable supplied	Unit standalone	215dx178wx155h mm
WiFi+ USB Optional		Weight	1.31kg
Drivers and Software Development Kits		Packed size	240x210x200mm, 1.7kg
SDK availability	Windows, Android, IOS	Warranty	
Drivers	Win Seagull, Linux, Mac	Warranty	12 Month Return to Base