



## Q3X

### Performance levels in a modern design product

Q3X is the ideal solution for those customers searching for the latest performance levels in a modern design product. The thermal head provides excellent graphic printing quality and lower consumption. The cutter has been designed to optimize the product performance, both in terms of efficiency and reliability, and meets the most demanding operating requirements. Its elegant design, developed to perfectly match any environment, is combined with high technological contents. It prints on 80 mm wide thermal paper, with front ticket outlet. Serial / USB interface. Bluetooth and Wi-Fi interfaces available.

## TECHNICAL SHEET

	Q3X	Q3X Wi-Fi	Q3X Ethernet	Q3X Bluetooth
<b>Interfaces</b>	RS232+USB	RS232+USB+WI-FI	Ethernet	RS232+USB+Bluetooth
<b>Printing Method</b>	Thermal printing			
<b>Number of dots</b>	8 dots / mm			
<b>Resolution</b>	203 DPI			
<b>Printing (mm/sec)</b>	140			
<b>Auto-cutter</b>	Cutter life 1 million cuts Partial cut			
<b>Character set</b>	PC437, PC850, PC860, PC863, PC865, PC858 (euro)			
<b>Numbers of columns</b>	32    42    56			
<b>Characters</b>	2.25 x 3    1.75 x 3    1.25 x 3 (L x H mm)-Normal			
<b>Supported Barcode</b>	UPCA, UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QRCODE, PDF417		UPCA, UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417	
<b>Printing width</b>	72 mm			
<b>Printing Format</b>	Normal, height and width from 1x to 8x, reverse, underlined, script, bold			
<b>Printing Direction</b>	Straight 90°, 180°, 270°			
<b>Paper width</b>	80 mm			
<b>Paper weight</b>	from 55 gr/m <sup>2</sup> to 60 gr/m <sup>2</sup>			
<b>Paper thickness</b>	63 $\mu$ m			
<b>Roll Dimension</b>	max diam. 80 mm			
<b>Sensors</b>	Head temperature Paper presence Detection of black mark Cover open Low paper		Head temperature Paper presence Detection of black mark Cover open	
<b>Emulation</b>	CUSTOM / POS			
<b>Data Buffer</b>	20 KB			
<b>Flash Memory</b>	4 MB (+1 MB internal to the micro)		512 Kb	
<b>RAM Memory</b>	2 MB			
<b>Graphic Memory</b>	1 logo (576x910 dots)			
<b>Drivers</b>	Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit); OPOS; Windows Phone; Android™; iOS; macOSX		Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); OPOS; Windows Phone; Android™; iOS; macOSX	
<b>Software tools</b>	PrinterSet, Virtual COM, Custom Windows API			
<b>Power supply</b>	24 Vdc $\pm$ 10% (External power supply)			
<b>Medium consumption</b>	1 A (12.5% dots on)			
<b>DKD Function</b>	1 Drawer kickout			
<b>MTBF</b>	360,000 hours (electronic board)			
<b>Safety</b>	EN60950 +A1+A2+A3+A4			

	Q3X	Q3X Wi-Fi	Q3X Ethernet	Q3X Bluetooth
<b>Marks</b>			CE, RoHS Compliant	
<b>Dimensions</b>		150 mm (L) × 140 mm (W) × 117mm (H)		
<b>Weight</b>		0.9 Kg		

## MODELS



**911FF010100K33**  
PRINTER Q3X BTH IAP2 USB  
RS232

**911FF010100333**  
PRINTER Q3X USB RS232

**911FF010200B33**  
PRINTER Q3X WIFI USB RS232

**911FF010100533**  
PRINTER Q3X ETH

Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 10 October 2024